



**WEST MICHIGAN RUBBER & SUPPLY**  
**1.800.533.9677**  
**sales@westmichiganrubber.com**

**201**

**Transportation**

SAE 100R5 SAE J1402 AII, D.O.T. FMVSS 106 AII - AIR BRAKE



# Part Number	Hose I.D.		Hose O.D.		Working Pressure		Minimum Bend Radius		Weight		Vacuum Rating		Parkrimp	Field Attachable
	inch	mm	inch	mm	psi	MPa	inch	mm	lbs/ft	kg/m	of Hg	kPa	26 Series	20/22 Series
201-4	3/16	5	0.52	13	3000	21	3	75	0.15	0.22	28	95	•	•
201-5	1/4	6,3	0.58	15	3000	21	3-3/8	85	0.18	0.27	28	95	•	•
201-6	5/16	8	0.68	17	2250	15,7	4	100	0.23	0.34	28	95	•	•
201-8	13/32	10	0.77	20	2000	14	4-1/2	115	0.27	0.40	28	95	•	•
201-10	1/2	12,5	0.92	23	1750	12,2	5-1/2	140	0.37	0.55	28	95	•	•
201-12	5/8	16	1.08	27	1500	10,5	6-1/2	165	0.40	0.60	28	95	•	•
201-16	7/8	22	1.23	31	800	5,6	7-3/8	185	0.46	0.68	20	68	•	•
201-20	1-1/8	29	1.50	38	625	4,3	9	230	0.51	0.76	20	68	•	•
201-24	1-3/8	35	1.75	44	500	3,5	10-1/2	265	0.68	1.01	15	51	•	•
201-32	1-13/16	46	2.22	56	350	2,4	13-1/4	335	0.89	1.32	11	37	•	•
201-40	2-3/8	60	2.88	73	350	2,4	24	610	1.31	1.95	11	37	•	•
201-48	3	76	3.56	90	200	1,4	33	840	2.09	3.11	11	37	•	•

**Application:** Petroleum base hydraulic fluids and lubricating oils, diesel fuels and antifreeze solutions.

**Inner Tube:** Synthetic rubber.

**Reinforcement:** One fiber braid and one steel braid.

**Cover:** Fiber braid.

**Temperature Range:** -40°F to +302°F (-40°C to +150°C).

**Fittings:** 26 Series - pg. B-9.  
 20 Series - pg. B-127.  
 22 Series - pg. B-145.