



WEST MICHIGAN RUBBER & SUPPLY
1.800.533.9677
sales@westmichiganrubber.com

Artic Ortac



APPLICATION: A low-temperature hose construction for air, water, oil, kerosene, fuel oil, and some chemical operations where temperatures fall as low as -65°F (-54°C).

TUBE: Black low-temp, ECO oil-resistant synthetic rubber, RMA Class A (High Oil Resistance)

COVER: Black ultra-low temperature, ECO oil resistant synthetic rubber (with a blue stripe), RMA Class A (High Oil Resistance)

REINFORCEMENT: One textile braid

TEMPERATURE: -65°F to 180°F (-54°C to 82°C)

PACKAGING: 500' reels, maximum 3 pieces, 50' minimum length

BRANDING: Continuous brand example "9.5mm 3/8" Artic Ortac Plus 2.1 MPA/300 PSI Goodyear™ Made in the U.S.A."

COUPLINGS: Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

ORDER CODES: 536-275

ID		NOM. OD		MAX. WP		WEIGHT	
in.	mm	in.	mm	psi.	Mpa	lb./ft.	kg./m.
1/4	6.4	0.63	16	300	2.07	0.16	0.22
3/8	9.5	0.75	19.1	300	2.07	0.2	0.28
1/2	12.7	0.91	23.1	300	2.07	0.27	0.37
3/4	19.1	1.18	30	300	2.07	0.4	0.54
1	25.4	1.5	38.1	300	2.07	0.57	0.86