



**WEST MICHIGAN RUBBER & SUPPLY**  
**1.800.533.9677**  
**sales@westmichiganrubber.com**



Note: Service life may vary depending on operating conditions and type of material being conveyed.

**Service Temperature Range**

-40° F to 150° F

Actual service temperature range is application-dependent.



**Series BW**  
**“Blue Water”**  
 Multi-purpose  
 low temperature  
 suction and transfer hose

**Features & Benefits**

- **HMW PVC clear construction** — allows for visual confirmation that material is flowing.
- **HMW PVC body** — provides sub-zero flexibility... increased abrasion-resistance compared to standard PVC.
- **Smooth cover** — makes clamping easy. Convolute cover on 5" & 6" for greater flexibility.
- **Clear body with blue helix** — provides easy identification.

**General Applications**

- General water suction & transfer
- Construction, rental & mining
- Agricultural applications
- Irrigation lines
- Abrasive liquid applications

Series	ID (In.)	Nominal		OD (mm)	Working Pressure (PSI)		Vacuum Rating (In. Hg)		Approx. Bending Radius @ 68°F	Standard Length (Ft)	Approx. Wt. (lbs/ft.)
		ID (mm)	OD (In.)		68°F	104°F	68°F	104°F			
BW075	3/4	19.1	1.01	25.6	115	75	Full	28	3"	100	0.19
BW100	1	25.4	1.26	32.0	90	65	Full	28	3"	100	0.22
BW125	1 1/4	31.8	1.56	39.6	90	65	Full	26	4"	100	0.36
BW150	1 1/2	38.1	1.79	45.5	90	65	Full	26	5"	100	0.48
BW200	2	50.8	2.35	59.8	90	65	Full	26	7"	100	0.62
BW250	2 1/2	63.5	2.87	73.0	70	48	Full	26	8"	100	0.87
BW300	3	76.2	3.43	87.0	65	45	Full	26	10"	100	1.23
BW400	4	101.6	4.49	114.0	55	40	Full	26	15"	100	1.83
BW500	5	127.0	5.57	141.5	45	30	28	24	25"	100/20	2.42
BW600	6	152.4	6.69	170.0	40	25	28	22	30"	100/20	3.36