



**WEST MICHIGAN RUBBER & SUPPLY**  
**1.800.533.9677**  
**sales@westmichiganrubber.com**



NOTE: Service life may vary depending on operating conditions and type of material being conveyed.

**Service Temperature Range**

-40° F to 150° F

Actual service temperature range is application-dependent.

**Series CF**  
 “Cold Flex”  
 heavy duty  
 low-temperature  
 PVC general purpose  
 suction and transfer hose

**Features and Benefits**

- **Black HMW PVC convoluted construction** — provides great flexibility in sub-zero temperatures.
- **Smooth bore construction** — allows unrestricted material flow.
- All sizes full vacuum rated at 68°F.

**General Applications**

- Low temperature suction applications.
- Liquid manure handling.
- Septic tank cleaning.
- Dry fertilizer broadcasting.

Series	Nominal				Working Pressure (PSI)		Vacuum Rating (In. Hg)		Approx. Bending Radius @ 68°F	Standard Length (Ft)	Approx. Wt. (lbs/ft.)
	ID (In.)	ID (mm)	OD (In.)	OD (mm)	68°F	104°F	68°F	104°F			
CF150	1½	38.1	1.84	46.7	100	65	Full	28	3"	100	.40
CF200	2	50.8	2.41	61.2	100	65	Full	28	4"	100	.75
CF250	2½	63.5	2.93	74.5	90	55	Full	28	6"	100	.99
CF300	3	76.2	3.59	91.2	80	50	Full	28	7"	100	1.34
CF400	4	101.6	4.67	118.6	65	35	Full	28	11"	100	2.15
CF600	6	152.4	6.87	174.4	50	25	Full	28	18"	100/50/20	3.76