



WEST MICHIGAN RUBBER & SUPPLY
1.800.533.9677
sales@westmichiganrubber.com

Series
MILK/MILK-LT
 PVC food grade liquid milk transfer hose

Features and Benefits

- *Precision-controlled ID and OD dimensions* — facilitates insertion of sanitary fittings.
- **Clear PVC construction with white helix** — complies with all applicable FDA† and USDA★ requirements and 3-A Sanitary Standards¶... allows visual confirmation that material is flowing.
- **Smooth bore construction** — provides unrestricted flow and eliminates material build-up.
- **Smooth cover** — makes clamping easier.

General Applications

- Milk Suction.
- Transfer of liquid dairy products.
- Wine making.

NOTE: Service life may vary depending on operating conditions and type of material being conveyed.

Series MILK:
Service Temperature Range

-4° F to 150° F

Series MILK-LT:
Service Temperature Range

-40° F to 150° F

Actual service temperature range is application-dependent.



Series	Nominal				Working Pressure (PSI)		Vacuum Rating (Inches Hg)		Approx. Bending Radius @ 68°F	Standard Length (Ft)	Approx. Wt. (lbs/ft.)
	ID (In.)	ID (mm)	OD (In.)	OD (mm)	68°F	104°F	68°F	104°F			
MILK150	1½	38.1	1.79	45.5	75	50	Full	26	4"	100	.45
MILK200	2	50.8	2.33	59.2	75	50	28	25	6"	100	.63
MILK250	2½	63.5	2.87	73.0	55	40	28	24	10"	100	.81
MILK300	3	76.2	3.42	86.9	55	40	28	24	11"	100	1.18
MILK-LT200	2	50.8	2.33	59.2	75	50	28	25	5"	100	.65
MILK-LT250	2½	63.5	2.87	73.0	55	40	28	24	8"	100	.84

† **FDA** — CFR Title 21 Parts 170 to 199.

★ **USDA** — For use in Federally-inspected meat and poultry plants.

¶ **3-A Sanitary Standard** — No. 20-20, Multi-use plastic materials as product contact surfaces in equipment for production, processing and handling of milk and milk products.