



**WEST MICHIGAN RUBBER & SUPPLY**  
**1.800.533.9677**  
**sales@westmichiganrubber.com**

## Pliovic GS

**APPLICATION:** A lightweight, economical general purpose hose for carrying air, water, and many spray solutions. Pliovic is suitable for a wide range of industrial, construction, agricultural hand sprayers, and many multipurpose applications. Nonconductive, minimum electrical resistance greater than one (1) megohm per inch of hose length at 1000 Volts DC. Available in Pliovic GS construction or a thick cover, Pliovic Plus construction

**TUBE:** Black Pliovic, RMA Class B (Medium Oil Resistance)

**COVER:** Pliovic, smooth finish, RMA Class B (Medium Oil Resistance)

**REINFORCEMENT:** Spiral synthetic yarn

**TEMPERATURE:** -10°F to 158°F (-23°C to 70°C)

**PACKAGING:** 1/4"–1/2" 750' reels, maximum 3 pieces, 50' increments

5/8" 500' reels, maximum 3 pieces, 50' increments

3/4" 450' reels, maximum 3 pieces, 50' increments

1" 400' reels, maximum 3 pieces, 50' increments

Coupled assemblies available upon request. Contact hose marketing for availability on cut, coiled, and tied hose lengths.

**BRANDING:** Continuous brand example "Pliovic GS 3/8" ID (9.5 mm) XXX psi WP. Made in USA by Goodyear™."

**COUPLINGS:** Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

Order Codes: 540-350 (blue) / 540-357 (yellow) / 540-472 (black) / 540-358 (green) / 540-406 (red)

ID		NOM. OD		MAX. WP		WEIGHT	
in.	mm	in.	mm	psi.	Mpa	lb./ft.	kg./m.
1/4	6.4	0.45	11.4	300	2.07	0.06	0.09
5/16	7.9	0.59	15	300	2.07	0.11	0.16
3/8	9.5	0.6	15.2	300	2.07	0.09	0.13
1/2	12.7	0.78	19.8	300	2.07	0.15	0.22