



WEST MICHIGAN RUBBER & SUPPLY
1.800.533.9677
sales@westmichiganrubber.com

T130AK - T140AK* - Steel Wire Air Hose

APPLICATION

High pressure air hose for heavy-duty use in mines, quarries, construction and industry.

COVER

Yellow, SBR — abrasion and ozone resistant — pin pricked.

REINFORCEMENT

*High tensile steel cords - braided - 1/2" - 2"
 High tensile spiral steel wire. - 2 1/2" - 4"

TUBE

Black SBR/NBR — resistant to oil mist.

TEMPERATURE RANGE

-22°F (-30°C) to 176°F (+80°C)

STANDARD LENGTH

50 or 100 feet

BRANDING

ALFAGOMMA – T140 STEEL AIR (Black Letters)

Embossed – ALFAGOMMA – ITALY – T130 STEEL AIR

Nominal Specifications

SERIES NO.	NOMINAL ID		NOMINAL OD		APPROX. WT. lbs./100 ft.	MAX. REC. WP (PSI)	MIN. BEND RADIUS (in.)
	(in.)	(mm)	(in.)	(mm)			
* T140AK050	1/2	13	0.91	23	38	600	2 1/2
* T140AK075	3/4	19	1.10	28	40	600	4
* T140AK100	1	25	1.34	34	50	600	5
* T140AK125	1 1/4	32	1.65	42	74	600	6 1/4
* T140AK150	1 1/2	38	1.89	48	86	600	7 1/2
* T140AK200	2	51	2.52	64	136	600	10
T130AK250	2 1/2	63	3.27	83	240	450	12 1/2
T130AK300	3	76	3.78	96	286	450	15
T130AK400	4	102	4.80	122	413	450	20