



WEST MICHIGAN RUBBER & SUPPLY
1.800.533.9677
sales@westmichiganrubber.com

Tiger™ - TRF

Heavy Duty Rubber Blend Suction Hose

General Applications: • Septic handling • Water suction - heavy duty

- Slurry handling • Marine bilge discharge
- Abrasive material transfer – standard duty

Construction: Rubber blend tube with rigid PVC helix.

Service Temperature: -40°F (-40°C) to +150°F (+65.5°C)*

Features and Benefits:

- **Superior Rubber Compounds** – Tigerflex™ uses specially engineered compounds which give the ideal combination of light weight, flexibility, conductivity and superior long-lasting durability.
- **Superior Flexibility** - 15% more flexible than similar competitive hoses.** Easier to bend and maneuver in the septic tank.
- **Cold Weather Flexible** - Special compounds remain flexible in sub zero temperatures. Increased flexibility allows the hose to come off the truck more easily and provides easier handling for the operator.
- **Smooth Bore Construction** - eliminates material build-up inside.
- **Smooth Outer Cover** - Provides increased pressure rating and smooth surface for banding.
- **Static Dissipating Tube** - Specially formulated to help prevent the build-up of static electricity for added safety.



Made In USA

Nominal Specifications

Series	ID (in.)	ID (mm)	OD (in.)	OD (mm)	Working Pressure (PSI)		Vacuum Rating (in Hg)		Min. Bending Radius (in. @ 68°F)	Standard Lengths (ft.)	Weight (lbs/ft.)
					68°F	104°F	68°F	104°F			
TRF300	3	76.2	3.43	87	45	32	FULL	26	6	100	1.23

*Actual service temperature range is application dependent.

**Based on factory testing

NOTE: Service life may vary depending on operating conditions and type of material being conveyed.