



WEST MICHIGAN RUBBER & SUPPLY
1.800.533.9677
sales@westmichiganrubber.com

BLACK CLOTH-INSERTED SBR SHEET RUBBER

General Properties of SBR†

- Excellent physical properties.

† Properties shown based on Rubber Manufacturers Association Sheet Rubber Handbook, second edition.

SPECIFICATIONS:

Commercial grade black SBR sheet, with cloth reinforcement:

Style CI: 60 Duro hardness (Shore Durometer A)

Polymer: Styrene-Butadiene Rubber reinforced with 3.4 oz./sq. yd. nylon fabric

Common Name: Cloth-reinforced Black Rubber Sheet

ISO/ASTM Designation: SBR

Style	ASTM Specification (SI units)	Temp. Range	Ply	Durometer	Tensile Strength (PSI)	Finish
CI	D 2000 M2AA 603	-20°F to +170°F	1	55 – 65	600	Plate
CI	D 2000 M2AA 603	-20°F to +170°F	2	55 – 65	600	Plate
CI	D 2000 M2AA 603	-20°F to +170°F	3	55 – 65	600	Plate
CI	D 2000 M2AA 603	-20°F to +170°F	4	55 – 65	600	Plate

Item Number	Gauge x Width (Inches)	Fabric Plies	Avg. Length (Linear Ft./Roll)	Approx. Wt./Roll
CI-1P02 x 48 x 67	1/16" x 48"	1 Ply	67 ft.	132 lbs.
CI-1P04 x 48 x 36	1/8" x 48"	1 Ply	36 ft.	140 lbs.
CI-2P04 x 48 x 36	1/8" x 48"	2 Ply	36 ft.	140 lbs.
CI-2P06 x 48 x 18	3/16" x 48"	2 Ply	18 ft.	107 lbs.
CI-2P08 x 48 x 18	1/4" x 48"	2 Ply	18 ft.	140 lbs.
CI-3P06 x 48 x 18	3/16" x 48"	3 Ply	18 ft.	107 lbs.
CI-4P08 x 48 x 18	1/4" x 48"	4 Ply	18 ft.	140 lbs.