



WEST MICHIGAN RUBBER & SUPPLY
1.800.533.9677
sales@westmichiganrubber.com

NEOPRENE CLOTH-INSERTED SHEET RUBBER

General Properties of Neoprene[†]

- Excellent physical properties.

[†] Properties shown based on Rubber Manufacturers Association Sheet Rubber Handbook, second edition.

SPECIFICATIONS:

Commercial grade black neoprene sheet, with nylon reinforcement:

Style NCI: 60 Duro hardness (Shore Durometer A)

Polymer: Chloroprene reinforced with 3.4 oz./sq. yd. nylon fabric

Common Name: Nylon-reinforced Neoprene Sheet

ISO/ASTM Designation: CR

Style	ASTM Specification (SI units)	Temp. Range	Ply	Durometer	Tensile Strength (PSI)	Finish
NCI	D 2000 M2BC 607	-20°F to +180°F	1	55 – 65	1100	Plate
NCI	D 2000 M2BC 607	-20°F to +180°F	2	55 – 65	1100	Plate

ORDERING INFORMATION:

Item Number	Gauge x Width (Inches)	Fabric Plies	Avg. Length (Linear Ft./Roll)	Approx. Wt./Roll
NCI-1P02 x 36 x 67	1/16" x 36"	1 Ply	67 ft.	93 lbs.
NCI-2P04 x 36 x 36	1/8" x 36"	2 Ply	36 ft.	98 lbs.
NCI-2P06 x 36 x 36	3/16" x 36"	2 Ply	36 ft.	146 lbs.
NCI-2P08 x 36 x 36	1/4" x 36"	2 Ply	36 ft.	196 lbs.