



WEST MICHIGAN RUBBER & SUPPLY
1.800.533.9677
sales@westmichiganrubber.com

T202AA - 150 PSI EPDM Multi-Purpose Water Suction Hose



APPLICATION

Suction and delivery of non-corrosive liquids for irrigation, construction, fertilizers and lasso acid solutions.

COVER

Black weather and ozone-resistant EPDM rubber.

REINFORCEMENT

Spiralled high tensile textile cords and 4 highly flexible steel helix wires.

TUBE

Black EPDM rubber.

TEMPERATURE RANGE

-22°F (-30°C) to 176°F (+80°C)

STANDARD LENGTH

100 feet: 1" through 6" 20, 50 feet: 5"
 20, 25, 50 feet: 6" 20, 25 feet: 8"

BRANDING

ALFAGOMMA – ITALY – T202 10 BAR (150 PSI) GENERAL PURPOSE EPDM (in green letters)

Nominal Specifications

SERIES NO.	NOMINAL ID		NOMINAL OD		APPROX. WT. lbs./100 ft.	MAX. REC. WP (PSI)	MIN. BEND RADIUS (in.)
	(in.)	(mm)	(in.)	(mm)			
T202AA100	1	25	1.38	35	46	150	4
T202AA125	1 1/4	32	1.65	42	54	150	5
T202AA150	1 1/2	38	1.89	48	63	150	6
T202AA200	2	51	2.40	61	82	150	8
T202AA250	2 1/2	63	2.95	75	118	150	10
T202AA300	3	76	3.46	88	141	150	12
T202AA350	3 1/2	90	4.02	102	177	150	14
T202AA400	4	102	4.49	114	198	150	16
T202AA500	5	127	5.55	141	314	150	25
T202AA600	6	152	6.54	166	392	150	30
T202AA800	8	203	8.70	221	659	150	40

COUPLING SUGGESTIONS

Quick-Acting, pin lug, short shank couplings or combination nipples attached with single bolt, double bolt, wire or band type clamps.