



WEST MICHIGAN RUBBER & SUPPLY

1.800.533.9677

sales@westmichiganrubber.com

T750AA / T750AG - 150 PSI 4-Ply Sandblast Hose



APPLICATION

Designed to convey abrasive sand and shot blast material.

COVER

Black or green, conductive SBR/NR blend – abrasion and ozone resistant – pin pricked.

REINFORCEMENT

High tensile textile cords — 4-ply construction.

TUBE

Static conducting natural rubber, offering excellent abrasion resistance.

TEMPERATURE RANGE

-22°F (-30°C) to 176°F (+80°C)

STANDARD LENGTH

50 or 100 feet

WORKING PRESSURE

Constant Pressure — 10 Bar (150 PSI)

BRANDING

ALFAGOMMA – ITALY T750 – 10 BAR (150 PSI)

SANDBLAST Ω

Nominal Specifications - T750AA/AG 4-Ply

SERIES NO.	NOMINAL ID		NOMINAL OD		TUBE THICKNESS	APPROX. WT. lbs./100 ft.
	(in.)	(mm)	(in.)	(mm)		
T750AA/AG075	3/4	19	1.50	38	0.236	63
T750AA/AG100	1	25	1.89	48	0.283	97
T750AA/AG125	1 1/4	32	2.17	55	0.283	116
T750AA/AG150	1 1/2	38	2.36	60	0.260	132
T750AA200	2	51	2.87	73	0.260	167

NOTE: Tolerances according to RMA Class 311-A