



WEST MICHIGAN RUBBER & SUPPLY
1.800.533.9677
sales@westmichiganrubber.com

VITON SHEET RUBBER

General Properties of VITON®

- Excellent resistance to many concentrated acids.
- Excellent resistance to heat.

† Properties shown based on Rubber Manufacturers Association Sheet Rubber Handbook, second edition.

Note: VITON® is a registered trademark of DuPont Dow Elastomers.

SPECIFICATIONS:

Commercial grade black VITON® sheet:

Style VI70: 72 Duro hardness (Shore Durometer A)

Polymer: Hexafluoropropylene Vinylidene Fluoride

Common Name: Viton

ISO/ASTM Designation: FKM

Style	ASTM Specification (SI units)	Temp. Range	Durometer	Tensile Strength (PSI)	Elongation (%)	Finish
VI70	D 2000 M1HK 704	-14°F to +482°F	72	600	165%	Plate

ORDERING INFORMATION:

Item Number	Gauge x Width (Inches)	Avg. Length (Linear Ft./Roll)	Approx. Wt./Roll
VI70-01 x 36 x 30	1/32" x 36"	30 ft.	29 lbs.
* VI70-02 x 36 x 10	1/16" x 36"	10 ft.	19 lbs.
VI70-02 x 36 x 30	1/16" x 36"	30 ft.	58 lbs.
* VI70-03 x 36 x 10	3/32" x 36"	10 ft.	28 lbs.
VI70-03 x 36 x 30	3/32" x 36"	30 ft.	85 lbs.
* VI70-04 x 36 x 10	1/8" x 36"	10 ft.	37 lbs.
* VI70-04 x 36 x 15	1/8" x 36"	15 ft.	55 lbs.
VI70-04 x 36 x 30	1/8" x 36"	30 ft.	110 lbs.
* VI70-06 x 36 x 10	3/16" x 36"	10 ft.	57 lbs.
VI70-06 x 36 x 30	3/16" x 36"	30 ft.	170 lbs.
* VI70-08 x 36 x 10	1/4" x 36"	10 ft.	74 lbs.
* VI70-08 x 36 x 15	1/4" x 36"	15 ft.	111 lbs.
VI70-08 x 36 x 30	1/4" x 36"	30 ft.	222 lbs.