



WEST MICHIGAN RUBBER & SUPPLY

1.800.533.9677

sales@westmichiganrubber.com

WORM GEAR HOSE CLAMPS



- four-piece construction
- clamp meets SAEJ1508 which supercedes Mil Spec WW-C-440B
- screw design: 5/16" slotted hex head
- maximum recommended torque 50 in. lbs.

Style HSS material:

- band and housing: SAE 201/301 series stainless
- screw: SAE 300 series stainless

Band Width	Hose O.D.		Part #
	from	to	
1/2"	28/64"	50/64"	HSS6
	32/64"	58/64"	HSS8
	36/64"	1-4/64"	HSS10
	44/64"	1-16/64"	HSS12
	52/64"	1-32/64"	HSS16
	52/64"	1-48/64"	HSS20
	1-4/64"	2"	HSS24
	1-20/64"	2-16/64"	HSS28
	1-36/64"	2-32/64"	HSS32
	1-52/64"	2-48/64"	HSS36
	2-4/64"	3"	HSS40
	2-20/64"	3-16/64"	HSS44
	2-36/64"	3-32/64"	HSS48
	2-52/64"	3-48/64"	HSS52
	3-4/64"	4"	HSS56
	3-20/64"	4-16/64"	HSS60

Band Width	Hose O.D.		Part #
	from	to	
9/16"	3-36/64"	4-32/64"	HSS64
	1-56/64"	5"	HSS72
	2-32/64"	5-32/64"	HSS80
	3-8/64"	6"	HSS88
	3-40/64"	6-32/64"	HSS96
	4-8/64"	7"	HSS104
	5-40/64"	8-32/64"	HSS128
	7-8/64"	10"	HSS152
	9-24/64"	12-16/64"	HSS188
	10-8/64"	13"	HSS200
	10-56/64"	13-48/64"	HSS212
	11-40/64"	14-32/64"	HSS224
	12-24/64"	15-16/64"	HSS236
	13-8/64"	16"	HSS248
17-8/64"	20"	HSS312	

Band Width	Hose O.D.		Part #
	from	to	
5/16"	14/64"	40/64"	MAH4
	28/64"	50/64"	MAH6
	32/64"	58/64"	MAH8
	36/64"	1-4/64"	MAH10
	44/64"	1-16/64"	MAH12
	60/64"	1-32/64"	MAH16
	1-12/64"	1-48/64"	MAH20

MINIATURE WORM GEAR HOSE CLAMPS

- screw design: 1/4" slotted hex head
- maximum recommended torque 15 in. lbs.

Style MAH material:

- band and housing: SAE 300 series stainless
- screw: SAE 300 series stainless